

# PE Beams Hard Wired 40M

Fixed Lens PE Safety Beams—range up to 40 Metres



## PE BEAMS HARD WIRED

The PE Safety Beams Hard Wired consist of a transmitter and receiver unit mounted on opposite sides of the entrance.

The transmitter sends a modulated infra red beam to the receiver. When the beam is interrupted the receiver relay gives a signal to stop or open the door or gate.

The contacts of the relay are potential free and can be wired as normally opened or normally closed.

The long range beams are fixed lens and can operate up to 40 metres.

They are housed in an IP55 shock proof plastic enclosure —suitable for outdoor use.

## Technical Specifications

Specification	PE Beams Hard Wired 40M
<b>Power Supply</b>	12-24v AC/DC
<b>Power Consumption</b>	108mA @ 24Vac
<b>Maximum Distance</b>	40 Metre
<b>Contact Rating</b>	1A @ 24v ac
<b>Protection</b>	IP 55
<b>Dimensions</b>	80 x 42 x 20

Rotech supply all forms of door and gate automation

### Vehicle Access Control

- Booms Gates
- Sliding Gates
- Swing Gates
- Industrial Door Openers
- Solar Powered Gate Openers

### Pedestrian Access Control

- Full Height Turnstiles
- Waist Height Turnstiles
- Supermarket Gates/Turnstiles
- Wheelchair Access Gates
- Rapid Access Gates