


SafePass W30R Adjustable PE Beam

Wireless rotational infrared PE Safety Beam



The SafePass W30R adjustable infrared safety beam with a wireless transmitter provides a convenient and safe gate automation system for even the most challenging of installations.

The wireless receiver is the only component that needs to be connected to the power supply which means no digging across the driveway, saving both time and money. The W30R is compatible with 12VAC/DC and 24VAC/DC voltage.

The external 180 degree rotation means set up is easy, simply rotate to align. The great design and a 30 metre range makes the W30R PE safety beams a pleasure to work with.

The system is fail safe and with the very low power consumption. The batteries will last a minimum of two years and then when the battery power is low an on board buzzer will give a warning signal.




The SafePass W30R Adjustable PE Safety Beam features:

- External 180 degree rotation - simply rotate to align
- Quick, easy installation with built-in laser beam alignment system
- The transmitter is wireless and battery-operated saving time and money
- 30 meters operating range – ideal for almost any entrance gate
- Fully ant-proof and weather-resistant enclosure for greater reliability
- Transmitter provides audible feedback for easy setup and battery-low indication
- Low power consumption throughout the system for greater efficiency.

Technical Specifications

Specification	W30R Adjustable PE Beam
Transmitter Power Supply	2 x AA Alkaline Batteries (Supplied) Only replace with alkaline batteries; do not use rechargeable batteries with this product
Receiver	12-24VAC 12-30VDC
Rotation Angle	180 Degree
Receiver Power Consumption	30mA@ 12V DC
Transmitter Battery Life	Minimum 2 years
Battery Low Indication	Audible Beep
Specified Operating Distance	30 meters
Alignment	Automatic - 1m ² @ 10m (circular area - assumes parallel surface)
Output Contact	Fail-safe, N/C and N/O, potential free contact
Output Contact Rating	3A@ 30V DC Non-inductive
Operating Temperature	-20°C - +60°C
Operating Humidity	0 - 90° Non-condensing
Degree of Protection	IP66
Size	113(L)*46.79(W)* 47.72(H)mm

Dimensions (mm)



Rotech supply all forms of door and gate automation

Vehicle Access Control

- Booms Gates
- Sliding Gates
- Swing Gates
- Industrial Door Openers
- Solar Powered Gate Openers

Pedestrian Access Control

- Full Height Turnstiles
- Waist Height Turnstiles
- Supermarket Gates/Turnstiles
- Wheelchair Access Gates
- Rapid Access Gates

Fast | Safe | Secure