

SafePass PC50 PE Beam

Reflective PE Safety Beam



The PC50 Reflective PE Beam

The PC50 Reflective Safety Beam is a high quality compact unit housed in a durable IP67 ABS waterproof enclosure

The PE beam is supplied with a mounting bracket to allow for easy adjustment. Alignment of the beam is achieved through the setting of the potentiometer mounted on top of the PE beam.

The two LED's on top of the beam indicate the status as shown below. The other switch allows the contacts to be changed from N/O to N/C without changing the connections.

The maximum operating distance is 10 metres, input voltage is 12 – 240vdc or 24 – 240vac and the relay is rated at 3 amps.

Technical Specifications

Specification	PC50 Reflective PE Beam
Power Supply	12-240v DC 24-240v AC
Power Consumption	100mA
Maximum Distance	10 Metre
Contact Rating	3A @ 240v
Protection	IP 67
Dimensions	50 x 50 x 20



Rotech supply all forms of door and gate automation

Vehicle Access Control

- Booms Gates
- Sliding Gates
- Swing Gates
- Industrial Door Openers
- Solar Powered Gate Openers

Pedestrian Access Control

- Full Height Turnstiles
- Waist Height Turnstiles
- Supermarket Gates/Turnstiles
- Wheelchair Access Gates
- Rapid Access Gates

For more information: t: +61 07 3205 1123 | www.rotech.com.au | e: info@rotech.com.au

V1024